

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch												
Model	(LV3) 4.3L EcoTec3 V6		(L3B) 2.7L Turbo		(L82) 5.3L EcoTec3 V8		(L84) 5.3L EcoTec3 V8		(L87) 6.2L EcoTec3 V8		(LM2) Duramax 3.0L Turbo-Diesel I6	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
TC10543	3.42	7700 (3493)	3.42	6800 (3084)	3.42	9800 (4445)	3.23	9600 (4355)			3.23	7400 (3357)
							3.42 ¹	11300 (5126)				
TK10543	3.42	7500 (3402)	3.42	6600 (2994)	3.42	9600 (4355)	3.23	9200 (4173) ²	3.23	8800 (3992) ³	3.23	9000 (4082)
							3.42 ¹	11100 (5035)	3.42 ¹	12000 (5443)		
TC10743	3.42	7600 (3447)	3.42	6800 (3084)	3.42	9700 (4400)	3.23	9500 (4309)			3.23	7300 (3311)
							3.42 ¹	11300 (5126)				
TK10743	3.42	7400 (3357)	3.42	6600 (2994)	3.42	9500 (4309)	3.23	9200 (4173)	3.23	9000 (4082) ³	3.23	9000 (4082)
							3.42 ¹	11000 (4990)	3.42 ¹	12000 (5443)		
TC10753	3.42	7700 (3493)	3.42	6900 (3130)	3.42	9800 (4445)	3.23	9600 (4355)			3.23	7400 (3357)
							3.42 ¹	11300 (5126)				
TK10753	3.42	7500 (3402)	3.42	6700 (3039)	3.42	9600 (4355)	3.23	9300 (4218)	3.23	9300 (4218)	3.23	9000 (4082)
							3.42 ¹	11100 (5035)	3.42 ¹	12100 (5489)		
TC10903	3.42	7900 (3583)			3.42	10000 (4536)						
TK10903	3.42	7700 (3493)			3.42	9800 (4445)						

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission						
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)					
	12000 (5443)	12800 (5806)	13000 (5897)	15000 (6804)	16800 (7620)	17800 (8074)
(LV3) 4.3L EcoTec3 V6		3.42				

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission						
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)					
	12000 (5443)	12800 (5806)	13000 (5897)	15000 (6804)	16800 (7620)	17800 (8074)
(L3B) 2.7L Turbo	3.42					
(L82) 5.3L EcoTec3 V8				3.42		
(L84) 5.3L EcoTec3 V8				3.23	3.42 ¹	
(L87) 6.2L EcoTec3 V8				3.23		3.42 ¹
(LM2) Duramax 3.0L Turbo-Diesel I6			3.23 ⁴	3.23 ⁵		

1 - Requires (NHT) Max Trailering Package.
2 - AT4 Trailering Capacity is 9800 lbs.
3 - AT4 Trailering Capacity is 9200 lbs.
4 - 2WD models.
5 - 4WD models.

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

Automatic Transmission Ratings with 5th Wheel or Gooseneck Hitch												
Model	(LV3) 4.3L EcoTec3 V6		(L3B) 2.7L Turbo		(L82) 5.3L EcoTec3 V8		(L84) 5.3L EcoTec3 V8		(L87) 6.2L EcoTec3 V8		(LM2) Duramax 3.0L Turbo-Diesel I6	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
TC10543	3.42	7600 (3447)	3.42	6800 (3084)	3.42	9700 (4400)	3.23	9100 (4128)			3.23	7300 (3311)
							3.42 ¹	10200 (4627)				
TK10543	3.42	7400 (3357)	3.42	6600 (2994)	3.42	9500 (4309)	3.23	8100 (3674) ²	3.23	7300 (3311) ³	3.23	7000 (3175)
							3.42 ¹	8500 (3856)	3.42 ¹	9800 (4445)		
TC10743	3.42	7500 (3402)	3.42	6700 (3039)	3.42	9700 (4400)	3.23	8700 (3946)			3.23	7200 (3266)
							3.42 ¹	9800 (4445)				
TK10743	3.42	7300 (3311)	3.42	6500 (2948)	3.42	9500 (4309)	3.23	7800 (3538) ³	3.23	7000 (3175) ⁴	3.23	6900 (3130) ⁵
							3.42 ¹	9600 (4355)	3.42 ¹	9500 (4309)		
TC10753	3.42	7600 (3447)	3.42	6800 (3084)	3.42	9700 (4400)	3.23	8700 (3946)			3.23	7300 (3311)
							3.42 ¹	10400 (4717)				
TK10753	3.42	7400 (3357)	3.42	6600 (2994)	3.42	9500 (4309)	3.23	8300 (3765) ⁶	3.23	7400 (3357)	3.23	7000 (3175) ⁷
							3.42 ¹	10100 (4581)	3.42 ¹	10000 (4536)		
TC10903	3.42	7800 (3538)			3.42	10000 (4536)						
TK10903	3.42	7600 (3447)			3.42	9700 (4400)						

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission						
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)					
	12000 (5443)	12800 (5806)	13000 (5897)	15000 (6804)	16800 (7620)	17800 (8074)
(LV3) 4.3L EcoTec3 V6		3.42				

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission						
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)					
	12000 (5443)	12800 (5806)	13000 (5897)	15000 (6804)	16800 (7620)	17800 (8074)
(L3B) 2.7L Turbo	3.42					
(L82) 5.3L EcoTec3 V8				3.42		
(L84) 5.3L EcoTec3 V8				3.23	3.42 ¹	
(L87) 6.2L EcoTec3 V8				3.23		3.42 ¹
(LM2) Duramax 3.0L Turbo-Diesel I6			3.23 ⁸	3.23 ⁹		

1 - Requires RPO (NHT) Max Trailering Package.
2 - AT4 Trailering Capacity is 8200 lbs.
3 - AT4 Trailering Capacity is 7600 lbs.
4 - AT4 Trailering Capacity is 7100 lbs.
5 - AT4 Trailering Capacity is 6800 lbs.
6 - AT4 Trailering Capacity is 7800 lbs.
7 - AT4 Trailering Capacity is 7500 lbs.
8 - 2WD models.
9 - 4WD models.