

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

**Automatic Transmission Ratings with Ball Hitch**

Model	(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block		(L86) 6.2L EcoTec 3 V8 with AFM SIDI VVT, aluminum block <sup>1</sup>	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
<b>CC15706</b>	3.08	6600 (2994)	3.23	8400 (3810)
<b>CC15706 with NHT</b>	3.42 <sup>2</sup>	8600 (3901)		
<b>CK15706</b>	3.08	6400 (2903)	3.23	8100 (3674)
<b>CK15706 with NHT or Z71</b>	3.42 <sup>2</sup>	8400 (3810)		

Trailering capacity may be limited by tow vehicle ability to carry trailer tongue weight.  
Addition of trailer tongue weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).

**GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission**

Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)	
	12000 (5443)	14000 (6350)
<b>(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block</b>	3.08	3.42 <sup>3</sup>
<b>(L86) 6.2L EcoTec 3 V8 with AFM SIDI VVT, aluminum block</b>		3.23

1 - Included and only available with (WPK) RST 6.2L Performance Edition or (9U0) 6.2L Performance Package.

2 - With (NHT) Maximum Trailering Package.

3 - Included and only available with (NHT) Maximum Trailering Package or (Z71) Off-Road Package.