

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch		
Model	(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)
CC15753	3.42	9400 (4264)
CK15753	3.42	9200 (4173)

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission	
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)
	15000 (6804)
(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block	3.42

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

<b>Automatic Transmission Ratings with 5th Wheel or Gooseneck Hitch</b>		
<b>Model</b>	<b>(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block</b>	
	<b>Axle Ratio</b>	<b>Maximum Trailer Weight lbs. (kg)</b>
<b>CC15753</b>	3.42	9400 (4264)
<b>CK15753</b>	3.42	9000 (4082)

<b>GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission</b>	
<b>Engine</b>	<b>(GCWR) Gross Combination Weight Ratings lbs. (kg)</b>
	<b>15000 (6804)</b>
<b>(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block</b>	3.42