

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch		
Model	(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)
CC15906	3.08	6300 (2858)
CC15906 with NHT	3.42	8300 (3765)
CK15906	3.08	6000 (2722)
CK15906 with NHT or Z71	3.42	8000 (3629)

Trailering capacity may be limited by tow vehicle ability to carry trailer tongue weight.
Addition of trailer tongue weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) or Gross Vehicle Weight Rating (GVWR).

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission		
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)	
	11000 (4990)	14000 (6350)
(L83) 5.3L EcoTec3 V8 AFM DI VVT aluminum block	3.08	3.42 ¹

1 - Included and only available with (NHT) Maximum Trailering Package or (Z71) Off-Road Package.