Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

	Aut	tomatic Transmission Ratings	with Ball Hitch	
Model	(L96) Vor	tec 6.0L V8 SFI	(L5P) Duramax 6.	6L Turbo-Diesel V8
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight Ibs. (kg)
TC35743 w/SRW	4.10	13000 (5897)	3.73	13000 (5897)
TC35943 w/SRW	4.10	14100 (6396)	3.73	14500 (6577)
TC35943 w/DRW	4.10	13700 (6214)	3.73	20000 (9072)
TK35743 w/SRW	4.10	13000 (5897)	3.73	13000 (5897)
TK35943 w/SRW	4.10	13700 (6214)	3.73	15000 (6804)
TK35943 w/DRW	4.10	13400 (6078)	3.73	20000 (9072)

Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)			
	21100 (9571)	25300 (11476)	31300 (14198)	
(L96) Vortec 6.0L V8 SFI	4.10			
L5P) Duramax 6.6L Turbo- Diesel V8		3.73	3.73	

^{1 -} Requires dual rear wheels.

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

	Automatic Tr	ansmission Ratings with 5th V	heel or Gooseneck Hitch	
Model	(L96) Vor	tec 6.0L V8 SFI	(L5P) Duramax 6.	6L Turbo-Diesel V8
	Axle Ratio	Maximum Trailer Weight Ibs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
TC35743 w/SRW	4.10	14200 (6441)	3.73	17500 (7938)
TC35943 w/SRW	4.10	14000 (6350)	3.73	17400 (7893)
TC35943 w/DRW	4.10	13700 (6214)	3.73	23100 (10478)
TK35743 w/SRW	4.10	13900 (6305)	3.73	17200 (7802)
TK35943 w/SRW	4.10	13700 (6214)	3.73	17000 (7711)
TK35943 w/DRW	4.10	13300 (6033)	3.73	22700 (10297)

Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)			
	21100 (9571)	25300 (11476)	31300 (14198)	
(L96) Vortec 6.0L V8 SFI	4.10			
(L5P) Duramax 6.6L Turbo- Diesel V8		3.73	3.73	

^{1 -} Requires dual rear wheels.