

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch						
Model	(LCV) 2.5L I4 DI DOHC VVT		(LWN) 2.8L Direct-Injection Turbo-Diesel		(LGZ) 3.6L DI DOHC V6 VVT	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
T2M53 /T2N53/T2P53	4.10	3500 (1588)			3.42	7000 (3175) ¹
T2M43 /T2N43/T2P43	4.10	3500 (1588)			3.42	7000 (3175) ¹
T2T43 /T2U43/T2V43					3.42	7000 (3175) ¹
T2N43 /T2U43/T2P43/T2V43			3.42	7700 (3493) ²		
T2N43 /T2P43			3.42	7600 (3447) ³		
T2U43 /T2V43			3.42	7550 (3425) ³		

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission			
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)		
	8500 (3856)	12000 (5443)	12700 (5761)
(LCV) 2.5L I4 DI DOHC VVT	4.10		
(LWN) 2.8L Direct-Injection Turbo-Diesel			3.42
(LGZ) 3.6L DI DOHC V6 VVT		3.42	

1 - Requires (Z82) Trailering Package.

2 - 2WD models only.

3 - 4WD models only.