

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch						
Model	(L96) Vortec 6.0L V8 SFI		(LC8) 6.0L V8 SFI Gaseous		(LML) Duramax 6.6L Turbo Diesel V8	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
CC25743	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CC25943	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CK25743	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CK25943	4.10	13000 (5897)	4.10	13000 (5897)	3.73	14500 (6577)
CC25753	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CC25953	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CK25753	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CK25953	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CC25903	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)
CK25903	4.10	13000 (5897)	4.10	13000 (5897)	3.73	13000 (5897)

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission		
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)	
	20500 (9299)	24500 (11113)
(L96) Vortec 6.0L V8 SFI	4.10	
(LC8) 6.0L V8 SFI Gaseous	4.10	
(LML) Duramax 6.6L Turbo Diesel V8		3.73

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

<b>Automatic Transmission Ratings with 5th Wheel or Gooseneck Hitch</b>				
<b>Model</b>	<b>(L96) Vortec 6.0L V8 SFI</b>		<b>(LML) Duramax 6.6L Turbo Diesel V8</b>	
	<b>Axle Ratio</b>	<b>Maximum Trailer Weight lbs. (kg)</b>	<b>Axle Ratio</b>	<b>Maximum Trailer Weight lbs. (kg)</b>
<b>CC25743</b>	4.10	14300 (6486)	3.73	17400 (7893)
<b>CC25943</b>	4.10	14200 (6441)	3.73	17300 (7847)
<b>CK25743</b>	4.10	14000 (6350)	3.73	17100 (7757)
<b>CK25943</b>	4.10	13800 (6260)	3.73	16400 (7439)
<b>CC25753</b>	4.10	14500 (6577)	3.73	17600 (7983)
<b>CC25953</b>	4.10	14400 (6532)	3.73	17500 (7938)
<b>CK25753</b>	4.10	14200 (6441)	3.73	17300 (7847)
<b>CK25953</b>	4.10	14100 (6396)	3.73	17200 (7802)
<b>CC25903</b>	4.10	14800 (6713)	3.73	17900 (8119)
<b>CK25903</b>	4.10	14500 (6577)	3.73	17600 (7983)

<b>GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission</b>		
<b>Engine</b>	<b>(GCWR) Gross Combination Weight Ratings lbs. (kg)</b>	
	<b>20500 (9299)</b>	<b>24500 (11113)</b>
<b>(L96) Vortec 6.0L V8 SFI</b>	4.10	
<b>(LML) Duramax 6.6L Turbo Diesel V8</b>		3.73