

**2013 Chevrolet Truck Silverado 3500HD TRAILERING SPECS - Automatic Transmission with Ball Hitch**

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission with Ball Hitch				
Model	(L96) Vortec 6.0L Variable Valve Timing V8 SFI		(LML) Duramax 6.6L Turbo Diesel V8	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
<b>CC30903 w/SRW</b>	4.10	13000 (5897)		
<b>CC30903 w/DRW</b>	3.73	9600 (4355)		
	4.10	14100 (6396)		
<b>CC30953 w/SRW</b>	3.73	9500 (4309)	3.73	17300 (7847)
	4.10	13000 (5897)		
<b>CC30953 w/DRW</b>	3.73	9100 (4128)	3.73	16500 (7484)
	4.10	13600 (6169)		
<b>CC30743</b>	3.73	9500 (4309)	3.73	13000 (5897)
	4.10	13000 (5897)		
<b>CC30943 w/SRW</b>	3.73	9400 (4264)	3.73	13000 (5897)
	4.10	13000 (5897)		
<b>CC30943 w/DRW</b>	3.73	9000 (4082)	3.73	16500 (7484)
	4.10	13500 (6124)		
<b>CK30903 w/SRW</b>	3.73	9700 (4400)	3.73	13000 (5897)
	4.10	13000 (5897)		
<b>CK30903 w/DRW</b>	3.73	9300 (4218)	3.73	16000 (7258)
	4.10	13800 (6260)		
<b>CK30953 w/SRW</b>	3.73	9200 (4173)	3.73	13000 (5897)
	4.10	13000 (5897)		
<b>CK30953 w/DRW</b>	3.73	8900 (4037)	3.73	18000 (8165)
	4.10	13400 (6078)		
<b>CK30743</b>	3.73	9200 (4173)	3.73	13000 (5897)
	4.10	13000 (5897)		
<b>CK30943 w/SRW</b>	3.73	9100 (4128)	3.73	13000 (5897)
	4.10	13000 (5897)		
<b>CK30943 w/DRW</b>	3.73	8500 (3856)	3.73	18000 (8165)
	4.10	13000 (5897)		

Addition of trailer tongue weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) of Gross Vehicle Weight Rating (GVWR).

(Z82) Trailering equipment, heavy-duty, includes trailer hitch platform and trailer electrical connector.

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission				
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)			
	16000 (7258)	20500 (9299)	24500 (11113)	30500 (13835)
(L96) Vortec 6.0L Variable Valve Timing V8 SFI	3.73	4.10		
(LML) Duramax 6.6L Turbo Diesel V8			3.73	3.73 <sup>1</sup>
1 - With Dual Rear Wheels.				

**2013 Chevrolet Truck Silverado 3500HD TRAILERING SPECS - Automatic Transmission  
Ratings with 5th Wheel or Gooseneck Hitch**

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

Automatic Transmission Ratings with 5th Wheel or Gooseneck Hitch				
Model	(L96) Vortec 6.0L Variable Valve Timing V8 SFI		(LML) Duramax 6.6L Turbo Diesel V8	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
<b>CC30903 w/SRW</b>	4.10	14500 (6577)		
<b>CC30903 w/DRW</b>	3.73	9600 (4355)		
	4.10	14200 (6441)		
<b>CC30953 w/SRW</b>	3.73	9500 (4309)	3.73	17300 (7847)
	4.10	14000 (6350)		
<b>CC30953 w/DRW</b>	3.73	9200 (4173)	3.73	22800 (10342)
	4.10	13700 (6214)		
<b>CC30743</b>	3.73	9500 (4309)	3.73	17200 (7802)
	4.10	14000 (6350)		
<b>CC30943 w/SRW</b>	3.73	9400 (4264)	3.73	17300 (7847)
	4.10	13900 (6305)		
<b>CC30943 w/DRW</b>	3.73	9000 (4082)	3.73	22800 (10342)
	4.10	13500 (6124)		
<b>CK30903 w/SRW</b>	3.73	9700 (4400)	3.73	17400 (7893)
	4.10	14200 (6441)		
<b>CK30903 w/DRW</b>	3.73	9300 (4218)	3.73	23100 (10478)
	4.10	13800 (6260)		
<b>CK30953 w/SRW</b>	3.73	9200 (4173)	3.73	16900 (7666)
	4.10	13700 (6214)		
<b>CK30953 w/DRW</b>	3.73	8900 (4037)	3.73	22600 (10251)
	4.10	13400 (6078)		
<b>CK30743</b>	3.73	9200 (4173)	3.73	17000 (7711)
	4.10	13700 (6214)		
<b>CK30943 w/SRW</b>	3.73	9100 (4128)	3.73	16800 (7620)
	4.10	13600 (6169)		
<b>CK30943 w/DRW</b>	3.73	8700 (3946)	3.73	22300 (10115)
	4.10	13200 (5988)		

Addition of trailer tongue weight cannot cause vehicle weights to exceed Rear Gross Axle Weight Rating (RGAWR) of Gross Vehicle Weight Rating (GVWR).

5th wheel hitch is available as a dealer installed accessory.

(Z82) Trailering equipment, heavy-duty, includes trailer hitch platform and trailer electrical connector.

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

Automatic Transmission Ratings with 5th Wheel or Gooseneck Hitch				
Model	(L96) Vortec 6.0L Variable Valve Timing V8 SFI		(LML) Duramax 6.6L Turbo Diesel V8	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission				
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)			
	16000 (7258)	20500 (9299)	24500 (11113)	30500 (13835)
(L96) Vortec 6.0L Variable Valve Timing V8 SFI	3.73	4.10		
(LML) Duramax 6.6L Turbo Diesel V8			3.73	3.73 <sup>1</sup>
1 - With Dual Rear Wheels.				