Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch												
Model	(LV3) 4.3L EcoTec3 V6		(L3B) 2.7L Turbo		(L82) 5.3L EcoTec3 V8		(L84) 5.3L EcoTec3 V8		(L87) 6.2L EcoTec3 V8		(LM2) Duramax 3.0L Turbo- Diesel I6	
	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)
CC10543	3.42	7700 (3493)	3.42	6800 (3084)	3.42	9700 (4400)	3.23	9800 (4445)			3.23	7600 (3447)
							3.42	11500 (5216) <sup>1</sup>				
CK10543	3.42	7500 (3402) <sup>2</sup>	3.42	6600 (2994)	3.42	9500 (4309)	3.23	9600 (4355) <sup>3</sup>	3.23	9200 (4173) <sup>1</sup>	3.23	9300 (4218)
							3.42	11300 (5126) <sup>1</sup>	3.42	12000 (5443) <sup>1</sup>		
CC10743	3.42	7600 (3447)	3.42	6800 (3084)	3.42	9600 (4355)	3.23	9700 (4400)			3.23	7500 (3402)
							3.42	11400 (5171) <sup>1</sup>				
CK10743	3.42	7400 (3357) <sup>4</sup>	3.42	6700 (3039)	3.42	9500 (4309) <sup>5</sup>	3.23	9500 (4309) <sup>6</sup>	3.23	9100 (4128) <sup>1</sup>	3.23	9200 (4173)
							3.42	11300 (5126) <sup>1</sup>	3.42	11900 (5398) <sup>1</sup>		
CC10753	3.42	7700 (3493)	3.42	6800 (3084)	3.42	9700 (4400)	3.23	9800 (4445)			3.23	7600 (3447)
							3.42	11600 (5262) <sup>1</sup>				
CK10753	3.42	7500 (3402) <sup>2</sup>	3.42	6600 (2994)	3.42	9500 (4309)	3.23	9600 (4355)	3.23	9300 (4218)	3.23	9300 (4218)
							3.42	11400 (5171) <sup>1</sup>	3.42	13400 (6078) <sup>7</sup>		
CC10903	3.42	7900 (3583)			3.42	10000 (4536)						
CK10903	3.42	7700 (3493)			3.42	9800 (4445)						

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission											
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)										
	12000 (5443)	12800 (5806)	13000 (5897)	15000 (6804)	16800 (7620)	17800 (8074)	19100 (8664)				
(LV3) 4.3L EcoTec3 V6		3.42									
(L3B) 2.7L Turbo	3.42										
(L82) 5.3L EcoTec3 V8				3.42							
(L84) 5.3L EcoTec3 V8				3.23	3.42 <sup>1</sup>						
(L87) 6.2L EcoTec3 V8				3.23		3.42 <sup>1</sup>	3.42 <sup>8</sup>				
(LM2) Duramax 3.0L Turbo- Diesel I6			3.23 <sup>9</sup>	3.23 <sup>10</sup>							

- 1 Requires (NHT) Max Trailering Package.
- 2 Trail Boss models are rated for maximum trailering capacity of 7,400 lbs.
- 3 Models equipped with (MQB) 10-speed automatic are rated for maximum trailering capacity of 9,300 lbs. Trail Boss models are rated for maximum trailering capacity of 9,400 lbs.
- 4 Trail Boss models are rated for maximum trailering capacity of 7,300 lbs.
- 5 Trail Boss models are rated for maximum trailering capacity of 9,400 lbs.
- 6 Models equipped with (MQB) 10-speed automatic are rated for maximum trailering capacity of 9,200 lbs. Trail Boss models are rated for maximum trailering capacity of 9,400 lbs.
- 7 Requires (NHT) Max Trailering Package and 20" wheels and tires. When equipped with 18" wheels and tires, maximum trailering capacity of 12,100 lbs.
- 8 Requires Double Cab 4WD model, (NHT) Max Trailering Package and 20" wheels and tires.
- 9 2WD models.
- 10 4WD models.
- 11 Trail Boss models are rated for maximum trailering capacity of 9,300 lbs.

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 15 to 25% of the trailer weight is the recommended 5th Wheel or Gooseneck kingpin load.

Automatic Transmission Ratings with 5th Wheel or Gooseneck Hitch												
Model	Model (LV3) 4.3L EcoTec3 V6		(L3B) 2.7L Turbo		(L82) 5.3L EcoTec3 V8		(L84) 5.3L EcoTec3 V8		(L87) 6.2L EcoTec3 V8		(LM2) Duramax 3.0L Turbo- Diesel I6	
	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight lbs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)	Axle Ratio	Maximu m Trailer Weight lbs. (kg)	Axle Ratio	Maximu m Trailer Weight Ibs. (kg)
CC10543	3.42	7600 (3447)	3.42	6700 (3039)	3.42	9600 (4355)	3.23	9700 (4400)			3.23	7500 (3402)
							3.42	11400 (5171) <sup>1</sup>				
CK10543	3.42	7400 (3357) <sup>2</sup>	3.42	6500 (2948)	3.42	9200 (4173) <sup>3</sup>	3.23	9500 (4309) <sup>4</sup>	3.23	8000 (3629) <sup>1</sup>	3.23	7200 (3266)
							3.42	11200 (5080) <sup>1</sup>	3.42	9500 (4309) <sup>1</sup>		
CC10743	3.42	7500 (3402)	3.42	6700 (3039)	3.42	9600 (4355)	3.23	9600 (4355)			3.23	7400 (3357)
							3.42	10900 (4944) <sup>1</sup>				
CK10743	3.42	7300 (3311) <sup>5</sup>	3.42	6500 (2948)	3.42	9400 (4264) <sup>6</sup>	3.23	9400 (4264) <sup>7</sup>	3.23	7700 (3493) <sup>1</sup>	3.23	7100 (3221)
							3.42	11200 (5080) <sup>1</sup>	3.42	9000 (4082) <sup>1</sup>		
CC10753	3.42	7600 (3447)	3.42	6800 (3084)	3.42	9600 (4355)	3.23	9700 (4400)			3.23	7500 (3402)
							3.42	11500 (5216) <sup>1</sup>				
CK10753	3.42	7400 (3357) <sup>2</sup>	3.42	6600 (2994)	3.42	9300 (4218) <sup>8</sup>	3.23	9500 (4309)	3.23	7700 (3493) <sup>1</sup> 3	3.23	8700 (3946)
							3.42	11300 (5126) <sup>1</sup>	3.42	10300 (4672) <sup>9</sup>		
CC10903	3.42	7800 (3538)			3.42	9900 (4491)						
CK10903	3.42	7600 (3447)			3.42	9700 (4400)						

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission											
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)										
	12000 (5443)	12800 (5806)	13000 (5897)	15000 (6804)	16800 (7620)	17800 (8074)	19100 (8664)				
(LV3) 4.3L EcoTec3 V6		3.42									
(L3B) 2.7L Turbo	3.42										
(L82) 5.3L EcoTec3 V8				3.42							
(L84) 5.3L EcoTec3 V8				3.23	3.42 <sup>1</sup>						
(L87) 6.2L EcoTec3 V8				3.23		3.42 <sup>1</sup>	3.42 <sup>10</sup>				
(LM2) Duramax 3.0L Turbo- Diesel I6			3.23 <sup>11</sup>	3.23 <sup>12</sup>							

- 1 Requires (NHT) Max Trailering Package.
- 2 Trail Boss models are rated for maximum trailering capacity of 7,300 lbs.
- 3 Trail Boss models are rated for maximum trailering capacity of 9,100 lbs.
- 4 Models equipped with (MQB) 10-speed automatic are rated for maximum trailering capacity of 8,300 lbs. Trail Boss models are rated for maximum trailering capacity of 8,800 lbs.
- 5 Trail Boss models are rated for maximum trailering capacity of 7,200 lbs.
- 6 Trail Boss models are rated for maximum trailering capacity of 8,900 lbs.
- 7 Models equipped with (MQB) 10-speed automatic are rated for maximum trailering capacity of 8,000 lbs. Trail Boss models are rated for maximum trailering capacity of 8,600 lbs.
- 8 Trail Boss models are rated for maximum trailering capacity of 8,500 lbs.
- 9 Requires (NHT) Max Trailering Package and 20" wheels and tires. When equipped with 18" wheels and tires, maximum trailering capacity of 10,100 lbs.
- 10 Requires Double Cab 4WD model, (NHT) Max Trailering Package and 20" wheels and tires.
- 11 2WD models.
- 12 4WD models.
- 13 Trail Boss models are rated for maximum trailering capacity of 8,400 lbs.