

Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Receiver Hitch						
Model	(LCV) 2.5L DOHC 4-Cylinder SIDI (VVT) ¹		(LSY) 2.0L Turbo DOHC 4-Cylinder SIDI (VVT) ¹		(LGX) 3.6L DOHC V6 (VVT) ²	
	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)	Axle Ratio	Maximum Trailer Weight lbs. (kg)
TNB26 FWD SLE / TNJ26 AWD SLE	3.80	1000 (454) ³	3.47	1500 (680) ⁴	3.49	4000 (1814)
TND26 FWD SLT / TNL26 AWD SLT			3.47	1500 (680)	3.49	4000 (1814)
TNF26 Denali FWD / TNN26 Denali AWD					3.49	4000 (1814)
TNC26 AT4 AWD					3.49	4000 (1814)

1 - Maximum towing capacity when ordered with available (VR2) Trailer hitch.
2 - Maximum towing capacity when ordered with available (V92) Trailering Package.
3 - FWD model only.
4 - AWD model only.