Maximum trailer ratings are calculated assuming standard equipped vehicle, driver and required trailering equipment. The weight of optional equipment, passengers and cargo will reduce the maximum trailer weight your vehicle can tow. 10 to 15% of the trailer weight is the recommended trailer tongue load.

Automatic Transmission Ratings with Ball Hitch						
Model	del (LCV) 2.5L I4 DI DOHC VVT (LWN) 2.8L Direct-Injection Tu Diesel			(LGZ) 3.6L DI DOHC V6 VVT		
	Axle Ratio	Maximum Trailer Weight Ibs. (kg)	Axle Ratio	Maximum Trailer Weight Ibs. (kg)	Axle Ratio	Maximum Trailer Weight Ibs. (kg)
T2M53 /T2N53	4.10	3500 (1588)			3.42	7000 (3175) <sup>1</sup>
T2M43	4.10	3500 (1588)			3.42	7000 (3175) <sup>1</sup>
T2N43 (2WD model)	4.10	3500 (1588)	3.42	7700 (3493)	3.42	7000 (3175)
T2N43 (4WD model)			3.42	7550 (3425)	3.42	7000 (3175)
T2U43 / T2V43			3.42	7550 (3425) <sup>2</sup>	3.42	7000 (3175) <sup>1</sup>
T2P43			3.42	7550 (3425)	3.42	7000 (3175)

GCWR For Engine/Rear Axle Ratio Combination with Automatic Transmission					
Engine	(GCWR) Gross Combination Weight Ratings lbs. (kg)				
	12000 (5443)	12700 (5761)			
(LCV) 2.5L I4 DI DOHC VVT					
(LWN) 2.8L Direct-Injection Turbo-Diesel		3.42			
(LGZ) 3.6L DI DOHC V6 VVT	3.42				

<sup>1 -</sup> Requires (Z82) Trailering Package.

<sup>2 - 4</sup>WD models.